



Toll Free No.: 1800-210-7484
WhatsApp No.: +91 84510 57484
Email: tiles.customercare@prismjohnson.in
For Export Enquires, Email:
exports.customercare@prismjohnson.in

PRISM JOHNSON LIMITED

H & R JOHNSON (INDIA) DIVISION

Corporate Office:

7th Floor, Windsor, C. S. T. Road, Kalina,
Santacruz (East), Mumbai - 400 098, India.

Tel: +91-22-40647300


Website: www.hrjohnsonindia.com

Registered Office: 305, Laxmi Niwas Apartments, Ameerpet
Hyderabad - 500016, Telangana, India.

Download App



Download E-Catalogue



JOHNSON MARBONITE
PREFERRED OVER ITALIAN MARBLE

80x300, 80x240, 120x180, 60x120,
80x80, 60x60, 40x40 CM

BRO0724RXXM001-CC Cat/Marbonite/Rajkot/composite/July'24

— JULY-2024



The marvel of modern vitrification technology, the Johnson Marbonite range is superior to its natural counterparts both aesthetically and functionally. Not only are they easier to install, but also are easier to maintain and don't need re-polishing for many years unlike natural marble. What's more the Marbonite Double Charge & Full body range comes with the Stain Free property that makes them easier to maintain and looking fresh for years.

All vitrified tiles have micro pores on their surfaces. Despite continuous cleaning dirt particles can get accumulated in these pores causing stubborn stains on the surface. The Stain Free technology seals the micro pores thus limiting the chances of dirt accumulation and stains and making maintenance easier therefore. Elimination of micro pores also enhances the reflectivity of the tile surface, adding to its lustre.

Johnson Marbonite introduces Big Format slabs which come in 80x300, 80x240 & 120x180cm (15mm thickness), which gives your wall and floor an elegant and seamless look. These full body slabs used for kitchen countertop, bathroom top, lift frame etc.

Full body vitrified tiles are perfect for commercial & industrial as well as residential use. Being thicker than regular tiles, full body tiles are more durable and can withstand the brunt of heavy foot traffic. They last for years without wear and tear and are highly abrasion resistant.

Due to their versatility and high performance, vitrified full body tiles are high in strength and thickness, making them ideal for all public spaces.



80x300 -BIG FORMAT 00

80x240 -BIG FORMAT 00

120X180 -BIG FORMAT 00

ELEGANCE HIGH END

60X120 00

60X60 00

SOLID SURFACE (10 MM)

60X120 00

60X60 00

SOLID SURFACE

60X120 00

60X60 00

SOLID SURFACE (SMART)

60X60 00

DOUBLE CHARGE

60X120 00

80X80 00

60X60 00

OUTDOOR

60X60 00


40X40 00

SOLUBLE SALT

60X60 00

Colors shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to change the specifications without prior notice. Sometimes, variations in shade or size may occur which is inherent to the ceramic industry. Before fixing the tiles, we urge you to read and follow the fixing instructions given on the carton box of the tiles. The company will not take any responsibility and will not accept any complaints of shade, size or planarity once the tiles have been fixed.

Although every effort is made to ascertain that all the information provided in this brochure is accurate before printing, errors may still happen. Please contact the local branch office for updated information before placing orders. The information contained in this catalog is given in good faith. The Company takes no liability on account of any loss or damage either consequential or otherwise as a result of the information provided therein.



Full Body
Tiles



Polished & Matt
Surface Finishes



Fully
Vitrified




Residential &
Commercial
Flooring Options

80 X 300 CM

BIG FORMAT
(15MM)


80x300 CM | POLISHED
(FB)

BIANCO WHITE



360°
View

EBONY BLACK



360°
View

ELEMENT BLACK



360°
View



BIG FORMAT
(15MM)


80x300 CM | POLISHED
(FB)

ELEMENT WHITE




360°
View

NERO BLACK




360°
View

SUPER WHITE



360°
View

GRAPHITE GRIS (MATT)



POLISHED



MATT

360°
View

BIG FORMAT
(15MM)

80x300 CM | MATT
(FB)

SPARKLE BARLEY



360°
View

SPARKLE WHITE




360°
View

SPARKLE CREMA



360°
View





Full Body
Tiles



Polished & Matt
Surface Finishes



Fully
Vitrified



Residential &
Commercial
Flooring Options

80 X 240 CM

BIG FORMAT
(15MM)

80x240 CM | POLISHED
(FB)

EBONY BLACK



360°
View

MONOLITH TERAZO WHITE




360°
View

SPARKLE CHOCO



360°
View

SUPER WHITE




360°
View

BIG FORMAT
(15MM)

80x240 CM | MATT/POLISHED
(FB)

GRAPHITE GRIS



ELEMENT BLACK



ELEMENT WHITE



ROYAL GRIS



BIG FORMAT
(15MM)

80x240 CM | MATT/POLISHED
(FB)

ROYAL IVORY



ROYAL MUSHROOM



ROYAL VERDE



SPARKLE BARLEY



SPARKLE CREMA




SPARKLE WHITE



BIG FORMAT
(15MM)

80x240 CM | POLISHED
(DSB)

BIANCO WHITE



360°
View

FUSION BLACK A



360°
View

FUSION BLACK B



360°
View

FUSION WHITE A



360°
View

FUSION WHITE B



360°
View

GREEN LAIDER F1*



360°
View

BIG FORMAT
(15MM)

80x240 CM | POLISHED
(DSB)

MARBLE CALCUTTA ORO*



360°
View

MARBLE MARQUINA*



360°
View

NERO BLACK



360°
View

STATUARIO ICE*



360°
View

BIG FORMAT
(15MM)

80x240 CM | MATT
(DSB)

MARBLE CALCUTTA NATURAL



360°
View

MARBLE LILAC WHITE



360°
View

TRAVERTINE CREMA



360°
View





Full Body
Tiles



Polished & Matt
Surface Finishes



Fully
Vitrified



Residential &
Commercial
Flooring Options

120 X 180 CM

BIG FORMAT
(15MM)

120x180 CM | POLISHED
(DSB)

BLISS WHITE



360°
View

ICONIC GREY



360°
View

CLOUDY CREMA



360°
View



BIG FORMAT
(15MM)

120x180 CM | POLISHED
(DSB)

MAJESTIC WHITE



360°
View

NOVA MARFIL



360°
View

MIRAZE NATURALA



360°
View

SMOKE WHITE



360°
View

BIG FORMAT
(15MM)

120x180 CM | POLISHED
(DSB)

TOLSTOY IVORY



NEW



360°
View

VENICE GREY



NEW



360°
View

TRAVERTINO BEIGE



NEW



360°
View

VIETNAM WHITE



NEW



360°
View



**ELEGANCE
HIGH END**

60 X 120 | 60 X 60 CM

ELEGANCE
HIGH END

60x120 CM | POLISHED

ELEGANCE ALMOND



360°
View

ELEGANCE FOSSIL



360°
View

ELEGANCE LIGHT GREY




360°
View



ELEGANCE
HIGH END


60x120 CM | POLISHED

ELEGANCE NERO



360°
View

ELEGANCE PINK




360°
View

ELEGANCE PISTA



360°
View

ELEGANCE STEEL GREY



360°
View

ELEGANCE WHITE



360°
View

ELEGANCE
HIGH END

60x60 CM | MATT/POLISHED

ELEGANCE AQUA




ELEGANCE BIANCO



ELEGANCE OLIVE



ELEGANCE COFFEE



ELEGANCE MUSHROOM



ELEGANCE BRICK



ELEGANCE NERO



SOLID SURFACE (10MM)

60 X 120 | 60 X 60 CM



Colour Options
with S&P Designs



Polished & Matt
Surface Finishes



Fully
Vitrified

SOLID
SURFACE

60x120 CM | MATT (10 MM)
(FB)

LIGHT GREY




360°
View

S&P IVORY



360°
View

S&P BLACK



360°
View

S&P CREMA



360°
View



SOLID
SURFACE

60x120 CM | MATT (10 MM)
(FB)

S&P PASTEL BROWN



360°
View

S&P SILVER




360°
View

S&P SNOW



360°
View

SUPER WHITE



360°
View

VANTA BLACK



360°
View

VERDE



360°
View

SOLID
SURFACE

60x60 CM | MATT (10 MM)
(FB)

LIGHT GREY



360°
View

S&P BLACK



360°
View

S&P CREMA




360°
View

S&P FOSSIL



360°
View

S&P IVORY



360°
View

S&P PASTEL BROWN



360°
View



SOLID
SURFACE

60x60 CM | MATT (10 MM)
(FB)

S&P SILVER



360°
View

S&P SNOW



360°
View

VERDE



360°
View



SOLID SURFACE

60 X 120 | 60 X 60 CM



SOLID
SURFACE

60x120 CM | MATT/POLISHED
(FB)

S&P GREY (POLISHED) ●




360°
View

LIGHT GREY



360°
View

S&P BLACK



360°
View



SOLID
SURFACE

60x120 CM | MATT/POLISHED
(FB)

S&P CREMA




S&P SILVER



S&P IVORY




S&P SNOW



S&P PASTEL BROWN




SPARKLE WHITE ●



SOLID
SURFACE

60x120 CM | MATT/POLISHED
(FB)

SUPER WHITE



MATT



POLISHED



View

VANTA BLACK



View

VERDE



MATT



POLISHED



View



SOLID
SURFACE


60x60 CM | POLISHED
(FB)

LIGHT GREY



360°
View

S&P BLACK



360°
View

S&P CREMA



360°
View

S&P FOSSIL



360°
View

S&P IVORY



360°
View

S&P PASTEL BROWN



360°
View



SOLID
SURFACE

60x60 CM | POLISHED
(FB)

S&P SILVER



360°
View

S&P SNOW




360°
View

VERDE



360°
View

PLATINA S&P IVORY (MATT)



NEW



360°
View

PLATINA S&P SPARKLE (MATT)



NEW



360°
View

PLATINA S&P CREMA (MATT/POLISHED)




NEW



360°
View

PLATINA S&P WHITE (MATT/POLISHED)



NEW



360°
View

SOLID
SURFACE

60x60 CM | RUSTIC
(FB)

PLAIN CREMA



360°
View

PLAIN LT GREY



360°
View

PLAIN VERDE



360°
View

S & P FOSSIL



360°
View

S & P NERO



360°
View


S & P SNOW



360°
View



SOLID SURFACE (SMART)



60 X 60 CM

SOLID
SURFACE
(SMART)


60x60 CM | POLISHED
(FB)

PASTEL ALMOND




360°
View

PASTEL BLACK




360°
View

PASTEL BLUE



360°
View

PASTEL BRONZE




360°
View

PASTEL GREEN



360°
View

S & P SNOW



360°
View



SOLID
SURFACE
(SMART)


60x60 CM | POLISHED
(FB)

S&P DARK GREY



360°
View

S&P GREEN CHILLY




360°
View

S&P LIGHT GREY




360°
View

S&P RED CHILLY



360°
View

S&P SAND



360°
View



DOUBLE CHARGE

60 X 120 | 80 X 80 | 60 X 60 CM



Stain
Free



Fully
Vitrified



Brighter
& Stronger
Tiles



Residential &
Commercial
Flooring Options

DOUBLE
CHARGE

60x120 CM | POLISHED

ALBIZA BEIGE



360°
View

ALBIZA GREY



360°
View

ALBIZA NATURA



360°
View



DOUBLE
CHARGE


60x120 CM | POLISHED

ALBIZA NERO



360°
View

ALBIZA ROSO



360°
View

ALBIZA WHITE



360°
View

ALMAZE BROWN



360°
View

ALMAZE CREMA



360°
View

ALMAZE SLATE



360°
View

DOUBLE
CHARGE

60x120 CM | POLISHED

ALMAZE WHITE




360°
View

ALTIS CREMA




360°
View

ALTIS WHITE



360°
View

ALTIS BLACK



360°
View

ALTIS NERO



360°
View

ANGLO CARAMEL



360°
View

DOUBLE
CHARGE

60x120 CM | POLISHED

ANGLO GOLD



360°
View

ANGLO MINT



360°
View

ANGLO WHITE




360°
View

DRAGON AQUA



360°
View

DRAGON CREMA



360°
View

DRAGON ROSE



360°
View

DOUBLE
CHARGE

60x120 CM | POLISHED

DRAGON WHITE



360°
View

FLORAL BUTTERSCOTCH



360°
View

FLORAL CREMA



360°
View



DOUBLE
CHARGE

60x120 CM | POLISHED

FLORAL FOREST



360°
View

FLORAL GREY



360°
View

FLORAL WHITE



360°
View

NERON SNOW



360°
View

PERLIN AZUL



360°
View

PERLIN BROWN ●



360°
View

DOUBLE
CHARGE

60x120 CM | POLISHED

PERLIN CREMA



360°
View

PERLIN GOLD



360°
View

PERLIN NERO ●



360°
View

PERLIN OLIVE ●



360°
View

PERLIN PINK



360°
View

PERLIN SLATE



360°
View

DOUBLE
CHARGE


60x120 CM | POLISHED

PERLIN WHITE



360°
View

PRISM ALEXA WHITE




360°
View

PRISM FLOW WHITE



360°
View

PRISM PLAIN WHITE



360°
View

TORINO AQUA



360°
View

TORINO ASH




360°
View

DOUBLE
CHARGE

60x120 CM | POLISHED

TORINO BEIGE



360°
View

TORINO ROSE



360°
View

TORINO BIANCO



360°
View

TORINO MAPLE



360°
View



DOUBLE
CHARGE

80x80 CM | POLISHED

ALBANO LEMON ●



360°
View

ALBANO ROSSEL ●



360°
View

ALBANO WHITE




360°
View

DRAGON WHITE



360°
View

ELENTA SNOW ALLURE



360°
View

PEARL WHITE ●



360°
View

SPIDER CREMA



360°
View

SPIDER WHITE



360°
View



DOUBLE
CHARGE

60x60 CM | POLISHED

ALBITO ALMOND



360°
View

ALBITO BASIL



360°
View

ALBITO BLACK



360°
View

ALBITO COFFEE



360°
View

ALBITO FOSSIL



360°
View


ALBITO GARNET



360°
View



ALBITO HAZEL ●



360°
View

ALBITO LATTE




360°
View

ALBITO PEACH ●



360°
View

ALBITO ROSSEL



360°
View

ALBITO LEMON LT



360°
View

ALBITO MIST



360°
View

ALBITO WHITE



360°
View

ANGLO CARAMEL



360°
View

ALBITO NATURA



360°
View

ALBITO NERO



360°
View

ANGLO MINT



360°
View

ARNAVA CREMA



360°
View

ARNAVA NERO



360°
View

ARNAVA OLIVE



360°
View

ARNAVA PINK



360°
View

ARNAVA ROSSEL



360°
View

ARNAVA VERDE



360°
View

ARNAVA WHITE



360°
View

ELENTA SERENITY SNOW



360°
View

ELENTA SICILIA CREMA



360°
View

FLORAL BUTTERSCOTCH



360°
View

FLORAL CREMA



360°
View

FLORAL FOREST



360°
View

FLORAL GREY



360°
View

DOUBLE
CHARGE

60x60 CM | POLISHED

FLORAL WHITE




360°
View

GENNEY CREMA



360°
View

GENNEY LAVA



360°
View

GENNEY NERO



360°
View

GENNEY PINK



360°
View

GENNEY SNOW



360°
View



DOUBLE
CHARGE

60x60 CM | POLISHED

GENNEY VERDE



360°
View

NERON GOLD



360°
View

PERLIN NERO



360°
View

PERLIN OLIVE



360°
View

NERON VERDE



360°
View

PERLIN AZUL ●



360°
View

PERLIN VERDE ●



360°
View

POLO GREEN



360°
View

PERLIN BROWN



360°
View

PERLIN CREMA ●



360°
View

POLO GREY



360°
View

POLO LEMON



360°
View

DOUBLE
CHARGE

60x60 CM | POLISHED

POLO SLATE



360°
View

PRISM ALEXA WHITE



360°
View

UNIQUE CREMA



360°
View

UNIQUE WHITE




360°
View

PRISM FLOW WHITE




360°
View

PRISM PLAIN WHITE



360°
View

ANTARTIC WHITE (MW)



360°
View

SICILIA WHITE



360°
View

SNOW WHITE



360°
View

OUTDOOR

60 X 60 | 40 X 40 CM



Robust
Vitrified Body



Skid
Resistant



40 x 40 mm
Tiles in 12 mm
Thickness




Exterior Floor
Application



Easy
Maintenance

BRICKS COTTO



360°
View

BRICKS GREY



360°
View

CUBICS BRONZE



360°
View

METTALIC BRONZE



360°
View

NATURAL BRICKS



360°
View

NATURAL STONE BRICKS



360°
View



OUTDOOR

60x60 CM | MATT
PARKING

PROTON COTTO



360°
View

PROTON COTTO HL



360°
View

PROTON IVORY



360°
View

SAND BEIGE



360°
View

SAND COTTO



360°
View

SAND CREMA



360°
View

SAND GREY




360°
View

SAND GRIS



360°
View

SAND WHITE



360°
View

SHELL GREY



360°
View

SHELL NATURAL



360°
View

SMOKE GREY



360°
View

SMOKE GREY HL




360°
View

SMOKE OFFWHITE



360°
View

TAURUS GRIS



360°
View

TAURUS METTALIC



360°
View

SMOKE OFFWHITE HL



360°
View

TAURUS CREMA



360°
View

TAURUS METTALIC HL



360°
View

URBANO COTTO




360°
View

TAURUS CREMA HL



360°
View

TAURUS GRIS HL



360°
View

URBANO GREY




360°
View

OUTDOOR


40x40 CM | POLISHED
(PARKING)

BALSA WOOD




360°
View

CLASSICO BROWN*



360°
View

CLASSICO COFFEE* ●




360°
View

CLASSICO GREY*



360°
View

CLASSICO PEACH*




360°
View

CLASSICO SILVER*



360°
View

CROSS BLUE ●




360°
View

CROSS ICE



360°
View

CROSS SMOKE



360°
View

CUBICS GRASS



360°
View



OUTDOOR

40x40 CM | POLISHED
(PARKING)

CUBICS GREY



360°
View

CUBOID TOPE



360°
View

GEO BEIGE



360°
View

GEO GRIS



360°
View

GEO PATTERN BROWN ●



360°
View

GEO PATTERN GREY



360°
View

IMPERIAL BIEGE



360°
View

IMPERIAL BLUE



360°
View

LINEAR GREY



360°
View

MATRIX ALMOND



360°
View

MATRIX BEIGE



360°
View

MATRIX BROWN



360°
View

MATRIX GRAPHITE



360°
View

MAZE BLUE



360°
View

MOROCCON CUBICS LEAF



360°
View

PEBBLES COFFEE



360°
View

OUTDOOR

40x40 CM | POLISHED
(PARKING)

PEBBLES GRASS



360°
View

PEBBLES NERO



360°
View

PEBBLES NTATO



360°
View

QUAD ALTIS



360°
View

QUAD BIEGE ●



360°
View

ROCK BEIGE



360°
View

ROCK CREMA ●



360°
View

RUG COTTO



360°
View

RUG GREY



360°
View

RUG SILVER



360°
View

SAVIO LEAF GRIS



360°
View

SAVIO LEAF PISTACHIO



360°
View

STONE BROWN



360°
View

STONE COTTO



360°
View

STONE GREY



360°
View

TERRAZO GRIS



360°
View

SOLUBLE
SALT

60x60 CM | POLISHED

ANDROMEDA




360°
View

APRICENA



360°
View

ASTORIA



360°
View

AVEO



360°
View

CLARA



360°
View

CREMA ATHOS



360°
View



SOLUBLE
SALT

60x60 CM | POLISHED

DEKOVEN



360°
View

ELENTRA



360°
View

TUSCANIA



360°
View

VENEER



360°
View

EMILIO



360°
View

IVORY




360°
View

ANDROMEDA (TR) - MATT



360°
View

IVORY (TR) - MATT



360°
View

ROSARIO



360°
View

STYRA



360°
View

A journey from tiles to lifestyles - measured in square feet

H&R Johnson (India) is a division of Prism Johnson Limited, one of India's foremost Integrated Building Materials conglomerates.

PRISM JOHNSON LIMITED



Established in 1958, Johnson is one of the oldest and trusted brands in the country. Built on the strong and unswerving foundations of quality and innovation, this trust has only grown in these decades gone by; and continues to grow. Starting with tiles, the brand soon diversified into offering lifestyle solutions in the realms of Engineered Marble & Quartz and Bath Solutions. There by becoming India's most Integrated Lifestyle Solutions brand. Every product that comes bearing the H&R Johnson insignia is a symbol of the same quality and innovation focused on adding value to the lives of our consumers.

Pioneering Innovations, A Way of Life

At H&R Johnson the term innovation is at the heart of everything we do. That's why it is backed by credible research. Every product attempts to fill in a void left by conventional offerings in the category, in an innovative manner. It's this value we place on cutting-edge innovation that makes us strive for more and eventually deliver more. A quality and a way of working that has redefine consumer lifestyles and expectations.

- Anti-skid & Water-repellent Tiles for Bathrooms
- Rectified Wall Tiles
- Johnson Marbonite - Vitrified Wall and Floor Tiles
- Joint Free Tiles
- Large Format Slabs
- Digitally Printed Wall & Floor Tiles
- Germ Free Tiles & Sanitaryware
- Exterior & Industrial Flooring Solutions

India's Most Integrated Tile Manufacturing Company



Self-owned Felspar Mines



Making Punches & Dies



Manufacturing of Soluble Salts and Inks

Being India's most trusted tiling brand requires that trust to be maintained in every stage of developing each and every product that bears the name of the brand. That's why at H&R Johnson, our Felspar Mines are Self-owned, the soluble salts and inks are manufactured in-house, and even the dies and punches are made in-house. All, so that every step in the process comes with the same quality and assurance, that you expect from us.



Manufacturing Excellence

Johnson has the most modern manufacturing units across strategic locations in India. Our manufacturing facilities employ the best technology from world leaders in tile manufacturing equipment. All our plants are ISO compliant with both 9001 and 14001 certifications as well as OHSAS 18001 certification.



Certifications



Johnson is India's largest tile manufacturer. It's commitment to quality, service and innovation is backed by certification from the world's leading accreditation bodies.

ISO 9001: 2015
For implementing a Quality Management System for the Manufacture and Supply of Ceramic Tiles.

ISO 45001: 2018
For implementing an Occupational Health & Safety Management System for the Manufacturing of Ceramic Tiles.

ISO 14001: 2015
For implementing an Environmental Management system for the Manufacturing of Ceramic Tiles

Certificate of Merit for Energy Conservation, Bureau of Energy Efficiency, Ministry of Power A Recognition for the efficient use of energy and its conservation.


Plant has received Safety award by National Safety Council

GreenPro is a product certification given by the Confederation of Indian Industry (CII) which signifies environmentally conscious life cycle of the production; certification for eco-friendly products that helps customers make an informed choice towards sustainable products.

Griha
Griha council is a joint initiative of Ministry of New and Renewable Energy, GOI and The Energy and Resources Institute of implement Griha. India's national rating system for sustainable habitats

Johnson Wall Tile Fixing Instructions

1. Plaster the surface to be tiled with a good finish and complete the rendering and curing at least two weeks prior to tiling. **DO NOT FIX TILES ON FRESH SURFACE.**
2. Before fixing the tiles, lay them out in the desired pattern and make sure that they give an acceptable blend of shade, colour and design. Also make sure that the tiles are acceptable to your satisfaction. Please note that certain amount of shade & size variation is inherent in all ceramic products.
3. The company bears no responsibility towards the tiles exposed to outside process like transfers, printing, firing etc.
4. For fixing these tiles, we recommend using an appropriate product from the range of tile fixing adhesives from the ARDEX ENDURA (INDIA) PVT. LTD. Please follow the adhesive manufacturer's recommendations and instructions for best results.
5. For fixing the setiles using sand and cement, follow the instruction given below:
 - a) Use cement and sand mortar in the ratio of 1:3. Add some water to create a consistent paste.
 - DO NOT USE NEAT CEMENT FOR FIXING TILES.**
 - b) Once the mixing has been completed, do not add more water and use the mixture within one hour.
 - c) Soak the tiles in clean water at least 30 minutes before fixing.
 - d) Remove the tiles from the water and allow them to drain to ensure that there is no film of water on the tile surface.
 - e) Apply a 15-20mm layer of bedding material evenly over an area of 1 square meter at a time on the surface of the area. Apply a fine slurry to the back of the tile to ensure proper and full bedding. Press gently for even adherence at the back of the tile. **DO NOT USE AN IRON HAMMER OR SOME HEAVY MATERIAL TO PRESS THE TILE.**
6. Mark and lay out the tiles from the center of the area to be laid so that cut tiles, if any, will be on the outer edges towards walls.
7. The nominal/work size of the tile is as printed on the carton. It is advisable to maintain a gap of 1mm to 2mm between two tiles to allow for possible expansion as per ISO tolerance norms.
8. Wait for 24 hours after fixing the tiles. After this period, fill the joints with cementitious or epoxy grouts from ARDEX ENDURA (INDIA) PVT. LTD.
9. Fifteen minutes after the grouting process, wipe off the excess grout with a damp sponge and polish the tiles with a soft, dry cloth.
10. Please note that wall tiles are specially manufactured for use on the wall only. **DO NOT FIX WALL TILES ON THE FLOOR.**
11. For cleaning tiles, use a moist cloth or sponge with water or diluted soap solution. You can also use tile & stone cleaners from ARDEX ENDURA (INDIA) PVT. LTD. **DO NOT SCRUB OR SCRATCH.**
12. **DO NOT USE ACID/ALKALI/SOLVENT/OILS/CLEANING POWDERS ETC. FOR CLEANING TILES.**
13. Please note: The company does not accept any liability in case of problems arising out of non-adherence to these tile fixing instructions.
14. **THE COMPANY WILL BEAR NO RESPONSIBILITY AFTER THE TILES ARE FIXED.**



NOTHING IN THESE INSTRUCTION IS A SUBSTITUTE FOR GOOD WORKMANSHIP AND SUPERVISION

TECHNICAL SPECIFICATION

S. No	Property	ISO 13006:2018 / EN 14411 Group Bla Requirement	ndian Standard IS 15622:2017 Group Bla Requirement	JOHNSON MARBONITE (DC) Value	Test Method
	Dimensions & Surface Quality	Whichever is less	Rectified edge		
1	Deviation in Length & Width	± 0.3% or ±2.0mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
2	Deviation in Thickness	± 5% or ±0.5mm	± 5 %	± 4%	ISO 10545-2 / IS 13630-1
3	Straightness of Sides	± 0.3% or ±0.8mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
4	Rectangularity	± 0.3% or ±1.5mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
5	Surface Flatness (Edge Curvature, Centre Curvature & Warpage)	± 0.4% or ±1.8mm	± 0.5 %	± 0.15%	ISO 10545-2 / IS 13630-1
6	Surface Quality	Min 95% free from visible defects	Min 95% free from visible defects	> 95% free from visible defects	ISO 10545-2 / IS 13630-1
	Physical Property				
7	Water Absorption	≤ 0.5%	Average ≤0.08%, Individual Max 0.1%	≤ 0.05%	ISO 10545-3/ IS 13630- 2
8	Modulus of Rupture	≥ 35 N/mm²	Average 35 N/mm², Individual 32N/mm², Min	≥ 38N/mm²	ISO 10545-4/ IS 13630-6
9	Breaking Strength	≥ 1300 N	Min1300 N	≥ 1500 N	ISO 10545-4 / IS 13630-6
10	Moisture expansion	report value	0.02 mm/m, Max	≤ 0.02 mm/m	ISO 10545-10 / IS 13630-3
11	Scratch hardness of surface (Moh's scale)	-	5, Min	≥ 5	IS 13630 -13
12	Coefficient of Linear Thermal Expansion	report value	Max, 6 x 10 ⁻⁶ K ⁻¹	≤ 6 x 10 ⁻⁶ K ⁻¹	ISO 10545-8/ IS 13630-4
13	Thermal Shock Resistance	report result	10 cycles Min	No Damage	ISO 10545-9 / IS 13630 -5
14	Impact Resistance	report value	0.55, Min	≥ 0.55	ISO 10545-5 / IS 13630-14
15	Coefficient of friction	-	Manufacturer to declare	≥0.3	ANSI A 326.3
16	Frost Resistance	report result	required if requested by purchaser	No Damage	ISO 10545-12 / IS 13630-10
17	Resistance to Deep Abrasion of Unglazed Tiles	≤ 175 mm³	Max 140 mm³	≤ 140mm³	ISO 10545- 6 / IS 13630-12
18	Bulk Density (g/cc)	-	2.2, Min	≥ 2.2	ISO 10545-3 / IS 13630-2
19	Color Resistance to UV light	report result	-	No change in color	DIN 51094
20	Chemical Property (cleansers except to cleansing agents containg Hydrofloric acids and its compounds)				
a	Resistance to Staining - Unglazed Tiles	-	Class 2, Min	Class 2, Min (BIS)	ISO 10545-14 / IS 13630-7
b	Resistance to Household Chemicals and Swimming Pool water cleansers - Unglazed tiles	UB	report resistance class	UA	ISO 10545-13 / IS 13630-7
c	Resistance to acids and alkalis (Unglazed Tiles)	report resistance class	report resistance class	UA	ISO 10545-13 /IS 13630 -7

* ISO / IS technical specifications for Johnson tiles are applicable only for premium /1st Quality tile
Please inspect all tiles prior to installation, company will not entertain any complaints once tiles are laid / fixed

TECHNICAL SPECIFICATION

S. No	Property	ISO 13006 :2018 / EN 14411 Group Bla Requirement	Indian Standard IS 15622:2017 Group Bla, Requirement	JOHNSON MARBONITE (FB) Value	Test Method
	Dimensions & Surface Quality	Whichever is less	Rectified edge		
1	Deviation in Length & Width	± 0.3% or ±2.0mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
2	Deviation in Thickness	± 5% or ±0.5mm	± 5 %	± 4%	ISO 10545-2 / IS 13630-1
3	Straightness of Sides	± 0.3% or ±0.8mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
4	Rectangularity	± 0.3% or ±1.5mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
5	Surface Flatness (Edge Curvature, Centre Curvature & Warpage)	± 0.4% or ±1.8mm	± 0.5 %	± 0.15%	ISO 10545-2 / IS 13630-1
6	Surface Quality	Min 95% free from visible defects	Min 95% free from visible defects	> 95% free from visible defects	ISO 10545-2 / IS 13630-1
	Physical Property				
7	Water Absorption	≤ 0.5%	Average ≤0.08%, Individual Max 0.1%	≤ 0.05%	ISO 10545-3/ IS 13630- 2
8	Modulus of Rupture	≥ 35 N/mm²	Average 35 N/mm², Individual 32N/mm², Min	≥ 38N/mm²	ISO 10545-4/ IS 13630-6
9	Breaking Strength	≥ 1300 N	Min1300 N	≥ 1500 N	ISO 10545-4 / IS 13630-6
10	Moisture expansion	report value	0.02 mm/m, Max	≤ 0.02 mm/m	ISO 10545-10 / IS 13630-3
11	Scratch hardness of surface (Moh's scale)	-	5, Min	≥ 5	IS 13630 -13
12	Coefficient of Linear Thermal Expansion	report value	Max, 6 x 10 ⁻⁶ K ⁻¹	≤ 6 x 10 ⁻⁶ K ⁻¹	ISO 10545-8/ IS 13630-4
13	Thermal Shock Resistance	report result	10 cycles Min	No Damage	ISO 10545-9 / IS 13630 -5
14	Impact Resistance	report value	0.55, Min	≥ 0.55	ISO 10545-5 / IS 13630-14
15	Coefficient of friction	-	Manufacturer to declare	≥0.3	ANSI A 326.3
16	Frost Resistance	report result	required if requested by purchaser	No Damage	ISO 10545-12 / IS 13630-10
17	Resistance to Deep Abrasion of Unglazed Tiles	≤ 175 mm³	Max 140 mm³	≤ 140mm³	ISO 10545- 6 / IS 13630-12
18	Bulk Density (g/cc)	-	2.2, Min	≥ 2.2	ISO 10545-3 / IS 13630-2
19	Color Resistance to UV light	report result	-	No change in color	DIN 51094
20	Chemical Property (cleansers except to cleansing agents containg Hydrofloric acids and its compounds)				
a	Resistance to Staining - Unglazed Tiles	-	Class 2, Min	Class 2, Min	ISO 10545-14 / IS 13630-7
b	Resistance to Household Chemicals and Swimming Pool water cleansers - Unglazed tiles	UB	report resistance class	UA	ISO 10545-13 / IS 13630-7
c	Resistance to acids and alkalis (Unglazed Tiles)	report resistance class	report resistance class	UA	ISO 10545-13 /IS 13630 -7

* ISO / IS technical specifications for Johnson tiles are applicable only for premium /1st Quality tile
Please inspect all tiles prior to installation, company will not entertain any complaints once tiles are laid / fixed

TECHNICAL SPECIFICATION

S. No	Property	ISO 13006:2018 / EN 14411 Group Bia Requirement	Indian Standard IS 15622:2017 Group Bia Requirement	Johnson Marbonite Value 15 mm	Test Method
	Dimensions & Surface Quality	whichever is less applicable. Rectified edge	Rectified edge		
1	Deviation in Length & Width	± 0.3% or ±1.0mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
2	Deviation in Thickness	± 5% or ±0.5mm	± 5 %	± 4%	ISO 10545-2 / IS 13630-1
3	Straightness of Sides	± 0.3% or ±0.8mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
4	Rectangularity	± 0.3% or ±1.5mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
5	Surface Flatness	± 0.4% or ±1.8mm	± 0.5 %	± 0.2%	ISO 10545-2 / IS 13630-1
6	Surface Quality	Min 95% free from visible defects	Min 95% free from visible defects	> 95% free from visible defects	ISO 10545-2 / IS 13630-1
	Physical Property				
7	Water Absorption	≤ 0.5%, individual Max 0.6%	Avaerage ≤0.08%, Individual 0.1%, Max	≤ 0.08%	ISO 10545-3/ IS 13630- 2
8	Modulus of Rupture	Average 35 N/mm ² , Individual 32N/mm ² , Min	Average 35 N/mm ² , Individual 32N/mm ² , Min	≥ 38N/mm ²	ISO 10545-4/ IS 13630-6
9	Breaking Strength	700 N Min for thickness < 7.5 mm, 1300 Min for thickness ≥ 7.5 mm	700 N Min for thickness < 7.5 mm, 1300 Min for thickness ≥ 7.5 mm	≥ 1500 N	ISO 10545-4 / IS 13630-6
10	Moisture expansion	report value	0.02 mm/m, Max	≤ 0.02 mm/m	ISO 10545-10 / IS 13630-3
11	Scratch hardness of surface (Moh's scale)	-	5, Min	≥ 6 (Matt surface)	IS 13630 -13
12	Resistance to Surface Abrasion of Glazed Tiles for Floor Application	report abrasion class & Cycle passed	Class II , Min	PEI III-V	ISO 10545-7 /IS 13630 -11
13	Coefficient of Linear Thermal Expansion	report value	Max, 6 x 10 ⁻⁶ K ⁻¹	Max, 6 x 10 ⁻⁶ K ⁻¹	ISO 10545-8/ IS 13630-4
14	Thermal Shock Resistance	report result	10 cycles Min	No Damage	ISO 10545-9 / IS 13630 -5
15	Crazing Resistance of Glazed Tiles	report result	4 cycles @7.5 bar Min	No Damage	ISO 10545-11/ IS 13630-9
16	Impact Resistance	report value	0.55, Min	≥ 0.55	ISO 10545-5 / IS 13630-14
17	Coefficient of friction	-	Manufacturer to declare	≥0.4	ANSI A 326.3
18	Frost Resistance	report result	required if requested by purchaser	No Damage	ISO 10545-12 / IS 13630-10
19	Bulk Density (g/cc)	-	2.2, Min	≥ 2.2	ASTM C373-16 / IS 13630-2
20	Color Resistance to UV light	report result	-	No change in color	DIN 51094
21	Chemical Property (cleansers except to cleansing agents containg Hydrofloric acids and its compounds)				
a	Resistance to Staining - Glazed Tiles	Min class 3	Class I, Min	Class 1 (IS)/ Class 3 (ISO)	ISO 10545-14 / IS 13630-8
b	Resistance to Household Chemicals and Swimming Pool water cleansers - Glazed tiles	GB	AA min	GA/AA	ISO 10545-13 / IS 13630-8
c	Resistance to acids and alkalis (Glazed Tiles)	report resistance class	report resistance class	GA	ISO 10545-13 /IS 13630 -8
22	Lead & Cadmium Release- for Glazed Tiles, where required	report value	-	Nil	ISO 10545-15

* ISO / IS technical specifications for Johnson tiles are applicable only for premium /1st Quality tile
Please inspect all tiles prior to installation, company will not entertain any complaints once tiles are laid / fixed

TECHNICAL SPECIFICATION

S. No	Test Description	ISO 13006:2018 / EN 14411 Group Bia Requirement	IS - 15622:2017 Group Bib	Johnson Marbonite Outdoor	Test Method
A)	Dimension Quality	whichever is less applicable. Rectified	Rectified		
1	Deviation in Length & Width	± 0.3% or ±1.0mm	± 0.1 %	± 0.1%	ISO 10545-2 / IS 13630-1
2	Deviation in Thickness	± 5% or ±0.5mm	± 5 %	± 4%	
3	Straightness of Sides	± 0.3% or ±0.8mm	± 0.1 %	± 0.1%	
4	Rectangularity	± 0.3% or ±1.5mm	± 0.1 %	± 0.1%	
5	Surface Flatness	± 0.4% or ±1.8mm	± 0.5 %	±0.3%	
6	Surface Quality	Min 95% free from visible defects from 1 meter distance under 300 lux light	Min 95% free from visible defects from 1 meter distance under 300 lux light	Min 95% free from visible defects from 1 meter distance under 300 lux light	
B)	Physical Property				
1	Water Absorption	≤ 0.5%, individual Max 0.6%	0.08%<E≤3, Individual 3.3 max	≤ 0.5%	ISO 10545-3 / IS 13630- 2
2	Scratch hardness of surface (Moh's scale)	-	≥5	≥6	IS 13630 part 13
3	Flexural Strength (Average MOR)	≥ 35 N/mm ² , Individual 32N/mm ² , Min	≥30N/mm ² , Individual 27 min	≥35N/mm ²	ISO 10545-4 / IS 13630-6
4	Breaking Strength	≥ 1300 N	≥1100N	≥ 1500 N	ISO 10545-4 / IS 13630-6
5	Impact Resistance	report value	≥ 0.55	≥ 0.55	ISO 10545-5 / IS 13630-14
6	Crazing Resistance	Report cycle	4 cycle	No damage	ISO 10545-11 / IS 13630- 9
7	Surface Abrasion Resistance (PEI Rating)	Report abrasion class	Class II, Min	Min PEI III - IV	ISO 10545-7 / IS 13630 - 11
8	Coefficient of friction	-	Manufacturer to declare	≥ 0.4	ANSI A 326.3
9	Bulk Density, in (g/cc)	-	≥ 2.0	> 2.2	ASTM C373-16 / IS 13630-2
10	Moisture expansion	Manufacturer to declare	Max 0.02 mm/m	≤ 0.02 mm/m	IS 13630-part 3 / ISO 10545-10
11	Frost Resistance	Manufacturer to declare	Manufacturer to declare	No Damage	ISO 10545-12 / IS 13630-10
12	Color Resistance to UV light	report result	report result	No change in color	DIN 51094
C)	Chemical Properties				
1	Resistance to Staining - Unglazed Tiles	-	Class 2, Min	Class 2, Min	ISO 10545-13 / IS 13630-8
	1) Resistance to Low concentrations of acids & alkalies	report resistance class	report resistance class	GLA/AA	
	2) Resistance to High concentrations of acids & alkalies	report resistance class	report resistance class	GHA/AA	
	3) Resistance to household chemicals and swimming pool salts	GB min	AA min	GB(ISO)/AA(BIS)	
2	Stain resistance	Min class 3	Class 1 min	Class 1 (IS)/ Class 3 (ISO)	ISO 10545-14 / IS 13630-8
D)	Thermal Properties				
1	Linear Thermal Expansion	Report value	≤7 x 10 ⁻⁶ K ⁻¹	≤7 x 10 ⁻⁶ K ⁻¹	ISO 10545-8/ IS 13630-4
2	Thermal shock resistance	-	10 Cycle, Min	10 Cycle, Min	ISO 10545-9 / IS 13630 -5

Ramp Test: Suitable for all kind of surfaces (Plain, structural.etc)
Slider (BOT -3000E Digital Tribometer) : suitable for plain / smooth surface and not working for structural / profiled surface

PACKING DETAILS

Product	Sizes	Finishes	No of Tiles/Box	Approx Area/ Box (sq m)	Approx Weight/Box (kgs)	Approx Cartons/ 20' Container	Approx Area per Container (sq m)
80X300 - 15mm	80X300	FB	1	2.4	84	321	770
80X240 - 15mm	80X240	FB & DSB	1	1.92	67.5	400	768
120X180 - 15mm	120X180	FB	1	2.16	77	350	756
60x120 Solid Surface	60x120	FB Polished	2	1.44	26	1038	1495
		FB Matt	2	1.44	29.5	915	1318
60X120 FB - 10mm	60x120	Matt	2	1.44	31	870	1253
60X120	60x120	DC Polished	2	1.44	25	1080	1555
60x120 - Elegance Series	60x120	Elegance High End	2	1.44	26	1038	1495
80x80 Elite	80x80	DC Polished	3	1.92	36	750	1440
60x60 Solid Surface	60x60	FB Polished	4	1.44	25	1080	1555
		FB Matt	4	1.44	30	900	1296
60x60 Elite	60x60	DC Polished	4	1.44	25.5	1058	1524
60X60 FB - 10mm	60x60	Matt	4	1.44	31	870	1253
60X60 FB	60x60	Rustic	4	1.44	27.5	981	1413
60X60 -12mm - Parking	60x60	Matt	3	1.08	27.5	981	1059
60x60 -Elegance Series	60x60	Polished	4	1.44	25	1080	1555
		Matt	4	1.44	25	1080	1555
60x60 - Smart Series	60x60	Polished	4	1.44	25.5	1058	1524
		Matt	4	1.44	26	1038	1495
400X400 - 11mm	40x40	Matt	5	0.80	18	1500	1200
60X60 SS	60x60	Polished	4	1.44	23.5	1148	1653
60X60 TR	60x60	Matt	4	1.44	24.5	1102	1587

YOU CAN ALSO REACH US AT

Region	Branch	Tel.:	Region	Branch	Tel.:
East	Kolkata	033-46021880	North	Jaipur	0141-2368329
	Bhubaneshwar	0674 6539836/37/2430240		Lucknow	0522-2721699
	Siliguri	9836065812		Varanasi	0542-2222620
	Guwahati	8135846661/7575900492		Patna	6202065659
	Ranchi	6202065659	South	Bengalure	080-22234310/080-22234330
West	Mumbai	022-40647500		Hyderabad	040-29802270 / 71 / 72
	Thane	022-25867600 / 666		Vijayawada	9666429666
	Pune	020-41301164 / 31		Vishakhapatnam	0891-2796376
	Aurangabad	8669600748		Tirupati	9121228960
	Ahmedabad	079-48480010		Kochi	0484-4871277
	Raipur	0771-4919129		Kozhikode	0422-4382698
	Indore	0731-4007441		Thiruvananthapuram	0471-2720141
	Jalandhar	0182-4505038 / 39		Chennai	044-28544116 / 28541881
North	Chandigarh	0172-4697100		Coimbatore	0422-4382698
	Delhi	011-49526600		Madurai	0452-4355584 / 4355594
				Trichy	9486718544

EXPERIENCE CENTERS

Location	Address	Tel.:
Kolkatta	HOUSE OF JOHNSON - 83 JBS Haldane Avenue, TOPSIA Trinity towers Kolkata - 700046	033-46021880
Guwahati	HOUSE OF JOHNSON - 1st Floor, Above Royal Riders Honda, Near Rahul Kata, Pub Bragaon, Garchuk, Guwahati - 781035	7575900492
Bhubaneshwar	HOUSE OF JOHNSON - Ray Tower, 1st Floor, N4/237, Indradhanu market, IRC Village, Nayapalli, Bhubaneshwar, Orissa - 751015	0674 6539836/37/2430240
Patna	HOUSE OF JOHNSON – SK Builders and colonizer Pvt.Ltd.,1st Floor, SK Palace, Saguna more, Bihar – 801503.	9702651243
Chandigarh	HOUSE OF JOHNSON - SCO 214, sector14, Panchkula, Haryana - 134109	0172-4637724
Delhi	HOUSE OF JOHNSON - First & Mezzanine Floor, B-1/G-3, Mohan Industrial Estate, Mathura Road, New Delhi - 110094.	11-49526600
Lucknow	HOUSE OF JOHNSON - 1st Floor, Prithvi Ratan Height,Plot No CP-4, Vijayant khand - 3, Gomtinagar Yojna, Lucknow - 226028	0522-2721699
Varanasi	HOUSE OF JOHNSON - Ashakunji, 1st floor, D59/103 D4, Opp Siddharth Complex, Sigra Mehmoorganj Road, Varanasi - 221010	0542-2222620
Aurangabad	House Of Johnson Aurangabad - Gut No 16/44, NH-211, Near Balapur Phata, Near Ramkisan Lawns, Beed Bypass Road Aurangabad 431005	8669600748
Pune	HOUSE OF JOHNSON - Sable House, Poona Snuff Factory, Sr. No 11A, Plot 408/4/5, Satara Road, Gultekadi, Pune - 411037	7350009364
Thane	HOUSE OF JOHNSON - Shop No.5, Gr.Floor, Cosmos Jewels, Near Dmart, Anand Nagar, Ghodbunder Road, Thane West - 400615	8424003247
Mumbai - Andheri	HOUSE OF JOHNSON – 1st flir, Bonanza, Sahar Plaza, Nr Hotel Kohinoor continental, J B Nagar, Andheri Kurla Road, Andheri East, Mumbai - 400059	8108030975
Ahmedabad	HOUSE OF JOHNSON - F 106-107, Shivalik Plaza, IIM Road, Panjrapole Cross Road, Ahmedabad, Gujarat - 380015	079-48480010
Indore	HOUSE OF JOHNSON - Shop No 5, 6, 7 and 8, Upper Ground Floor, Exotica, Shalimar Township, Village Niranjanpur, A. B. Road, Indore, Madhya Pradesh - 452001	0731-4007441
Raipur	HOUSE OF JOHNSON - 2nd Floor, MM Silver Plaza, Opp Udyog Bhawan, Ring Road - 1, Raipur, Chattisgarh - 492001	771-4919129
Coimbatore	HOUSE OF JOHNSON - Elysium Towers, Park Gate Rd, No. 21, ATT Colony, Gopalapuram, Coimbatore - 641018	0422-4382698
Chennai	HOUSE OF JOHNSON - 82, 84 & 86 Bascon Maeru, 1st floor, Kodambakkam High Road, Nungambakkam, Chennai - 600034	044-48611632
Kochi	HOUSE OF JOHNSON - Door no. 11/300 f, Next to VTJ Hyundai, NH 47 Kundanoor, Maradu, Kochi, Ernakulam - 682304	0484-4871277
Kozhikode	HOUSE OF JOHNSON - Tilal Tower, Near Nexa Showroom, Kudilthod, Malaparamba bypass, Kozikode, Kerala - 673017	0495-2357505
Thiruvananthapuram	HOUSE OF JOHNSON -1st Floor, Sreedhanya Apex, TC 22/3720 (4) Vellayambalam, Sasthamangalam PO, Thiruvananthapuram, Kerala - 695010	0471-2720141
Bengalure	HOUSE OF JOHNSON - No.39, Rajaram Mohan Roy Road , Opp. Kanteerava indoor Stadium, Bengalure - 560027	080-22234310/080-22234330
Bengalure	HOUSE OF JOHNSON - Dodda Banaswadi, Opp. New Baldwin Residential School, Bengalure-560043	080-41692976 / 41692060
Hyderabad	HOUSE OF JOHNSON - SP Jubilee Crown (3rd Floor) Plot - 1270, Road No.36, Jubilee Hills, Hyderabad – 500033	8897525143

For address and contact numbers of our Johnson Exclusive Showrooms and Authorized Retailers, please visit our website www.hrjindia.com